Product:
 U-835
 Revised Date: 04/27/15

 MSDS ID:
 R1102
 Replaces Date: 12/16/13

## 1. General Information

Product Code: R1102 Trade Name: U-835

Product Type: Acrylate/methacrylate functionalized urethane resin

Company: Designer Molecules, Inc.

10080 Willow Creek Rd. San Diego, CA 92131

Telephone: 858-348-1122

Emergency phone number (spill, leak, fire, exposure or accident):

US Domestic 800-424-9300 (CHEMTREC)

International +1 703-527-3887

### 2. Hazards Identification

#### **EMERGENCY OVERVIEW:**

#### **OSHA Hazards:**

Harmful by ingestion, Harmful by skin absorption, Irritant

### **GHS Classification:**

Acute toxicity, Oral (Category 4) Acute toxicity, Dermal (Category 4) Skin irritation (Category 2)

Eye irritation (Category 2A)

Specific target organ toxicity-single exposure (Category 3)

### **GHS Label Elements, including precautionary statements:**



Signal Word: Warning

H302 + H312: Harmful if swallowed or in contact with skin.

H315: Causes skin irritation.H319: Causes serious eye irritation.H335: May cause respiratory irritation.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P280: Wear protective gloves/protective clothing.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

## **HMIS Classification:**

Health Hazard: 2 Flammability: 1 Physical Hazards: 0

#### NFPA Rating:

Health Hazard: 2
Fire: 1
Reactivity Hazard: 0

Date Printed: 7/14/2015 Page 1 of 6

 Product:
 U-835
 Revised Date: 04/27/15

 MSDS ID:
 R1102
 Replaces Date: 12/16/13

**POTENTIAL HEALTH EFFECTS:** 

**INHALATION:** May be harmful if inhaled. Causes respiratory tract irritation.

**EYE CONTACT:** Causes eye irritation

**SKIN CONTACT:** Harmful if absorbed through skin. Causes skin irritation.

**SWALLOWING:** Harmful if swallowed.

## 3. Composition Information

COMPONENT CAS# CONCENTRATION

Modified urethane resin mixture ~ 100%

## 4. First Aid Measures

**SWALLOWING:** Do not induce vomiting. Give person large amounts of water. Get immediate

medical attention.

SKIN CONTACT: Wash area with soap and water. Remove contaminated clothing and shoes. Wash

or clean before reuse.

**INHALATION:** Remove person to fresh air. If breathing has stopped, perform artificial respiration. If

breathing is difficult, give oxygen. Get medical attention.

**EYE CONTACT:** Flush with water for 15 minutes. Get immediate medical attention.

**NOTES TO PHYSICIAN:** 

There is no specific antidote. Treatment of overexposure should be directed at

the control of symptoms and the clinical condition of the patient.

# 5. Fire and Explosion Hazard Data

FLASH POINT (method): > 400°F, 204°C, (closed cup)

**EXTINGUISHER METHOD:** Water spray, CO<sub>2</sub>, foam, dry chemical

**SPECIAL FIRE-FIGHTING PROCEDURES:** 

Fire fighters should wear NIOSH/MSHA approved pressure demand self-contained breathing apparatus. Decontaminate or discard any clothing that may contain chemical residues.

#### **UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Do not enter fire area without proper protection. See Section 10, Reactivity Data, for decomposition products possible. Fight fire from safe distance and protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Water may be ineffective in firefighting due to low solubility. Use water spray/fog for cooling. Pressure relief system may plug with solids, increasing risk of overpressure.

### 6. Accidental Release Measures

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Promptly absorb spill. Remove sources of ignition. Cover drains to prevent entry into waterways. Wear personal protective equipment (clothing and gloves) when handling spilled materials.

#### **PERSONAL PRECAUTIONS:**

Wear suitable protective equipment.

### **ENVIRONMENTAL PRECAUTIONS:**

This product is essentially insoluble in water. This material is resistant to rapid biodegradation. May be toxic to aquatic life. Avoid runoff to waterways and sewers.

Date Printed: 7/14/2015 Page 2 of 6

 Product:
 U-835
 Revised Date: 04/27/15

 MSDS ID:
 R1102
 Replaces Date: 12/16/13

## 7. Handling and Storage

**HANDLING:** Avoid contact with eyes.

Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

VENTILATION: General (mechanical) room ventilation is expected to be satisfactory for use at room

temperature. Special, local ventilation is recommended at points where vapors generated

at high temperatures may be vented to the workplace air.

STORAGE: Store at 5°C away from incompatible materials identified in the Stability and Reactivity

Section.

## 8. Exposure Controls and Personal Protection Measures

COMPONENT EXPOSURE LIMITS

ACGIH OSHA MFG Working

**Standard** 

Modified urethane resin not established not established not established

PERSONAL PROTECTION:

Respiratory: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and

ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use. If a respirator is used, a NIOSH/MSHA approved respirator with organic vapor/dust-mist

fume filters represents the minimum level of respiratory protection.

Hands: Solvent impermeable gloves. Eyes: Chemical safety goggles. Skin: Chemical-resistant clothing.

OTHER PROTECTIVE EQUIPMENT:

Wear disposable protective clothing to facilitate recovery of any materials spilled.

**ENGINEERING CONTROLS:** 

Ventilation: Local Exhaust:

Fume hood at point of generation with sufficient exhaust to remove material

from breathing zone.

**EXPOSURE LIMITS:** 

None established by OSHA, ACGIH or UCC

# 9. Physical / Chemical Characteristics

**APPEARANCE:** 

Physical State: Liquid
Color: Light yellow
Odor: Musty odor

**OTHER PROPERTIES:** 

Boiling Point:

Melting Point:

Not determined

Not determined

Not determined

Density (g/CC): 0.99

Vapor Pressure (mmHg): Not determined Vapor Density (air=1): Not determined

Volatile Organic Compounds: < 0.1 %

Date Printed: 7/14/2015 Page 3 of 6

 Product:
 U-835
 Revised Date: 04/27/15

 MSDS ID:
 R1102
 Replaces Date: 12/16/13

Solubility in water: Not determined Evaporation rate: Not determined

Percent volatile (weight): < 0.1 %

Decomposition Temperature: Not determined

## 10. Reactivity Hazard Data

STABILITY: Stable

**CONDITIONS TO AVOID:** Elevated temperatures in the presence of initiators

INCOMPATIBLE MATERIALS: Can react with strong oxidizing agents, strong Lewis or mineral

acid, free radical initiators, inert gasses, oxygen scavengers and strong mineral and organic bases, especially primary and

secondary amines.

**HAZARDOUS DECOMPOSITION PRODUCTS:** 

Acrid smoke-fumes/carbon monoxide/carbon dioxide and

perhaps other toxic vapors may be released during a fire

involving this product.

**HAZARDOUS POLYMERIZATION:** May occur.

# 11. Toxicological Information

#### **SWALLOWING:**

Acute effects: May cause nausea, abdominal pain, vomiting, headache, dizziness, shortness of

breath, weakness, leg cramps, restlessness, confusion, visual disturbances, drowsiness, coma, and death. There may be a delay of up to forty-eight hours

before the onset of symptoms.

**Test results:** Acute Toxicity: Toxicological testing has not been performed with this material.

<u>Chronic Toxicity:</u> Toxicological testing has not been performed with this material.

**SKIN ABSORPTION:** 

Acute effects: No evidence of harmful effects.

**Test results:** Acute Toxicity: Toxicological testing has not been performed with this material.

Chronic Toxicity: Toxicological testing has not been performed with this material.

**INHALATION:** 

Acute effects: Short-term harmful health effects are not expected from vapor generated at

ambient temperature.

**Test results:** Acute Toxicity: Toxicological testing has not been performed with this material.

Chronic Toxicity: Toxicological testing has not been performed with this material.

SKIN CONTACT:

Acute effects: Causes moderate irritation. Causes local discomfort, redness, possibly slight

swelling, and scaling. The effects of repeated exposure may cause sensitization

and allergic skin reaction.

Test results: Acute Toxicity: Toxicological testing has not been performed with this material.

Chronic Toxicity: Toxicological testing has not been performed with this material.

#### **EYE CONTACT:**

Date Printed: 7/14/2015 Page 4 of 6

 Product:
 U-835
 Revised Date: 04/27/15

 MSDS ID:
 R1102
 Replaces Date: 12/16/13

Acute effects: May cause irritation. Causes discomfort, pain, excessive blinking, tear production

and, marked excessive redness and swelling of the conjunctivae. Corneal injury may occur. Corneal injury may be severe, extensive and, if not treated promptly,

could result in permanent impairment.

**Test results:** Acute Toxicity: Toxicological testing has not been performed with this material.

Chronic Toxicity: Toxicological testing has not been performed with this material.

**SENSITIZATION:** 

**Test results:** Acute Toxicity: Toxicological testing has not been performed with this material.

Chronic Toxicity: Toxicological testing has not been performed with this material.

**MUTAGENICITY:** 

**Genetic toxicity** 

(in vitro): Acute Toxicity: Toxicological testing has not been performed with this material.

<u>Chronic Toxicity:</u> Toxicological testing has not been performed with this material.

12. Ecological Information

**POTENTIAL EFFECT ON ENVIRONMENT:** Do not allow to enter drains, sewers or watercourses.

MOBILITY: Insoluble POTENTIAL TO BIOACCUMULATE: Unknown

AQUATIC TOXICITY: None established

13. Disposal Considerations

WASTE DISPOSAL METHOD: Disposal should be in accordance with local, state of

national legislation.

**EMPTY CONTAINER WARNINGS:** Empty containers may contain product residue, follow

MSDS and label warnings even after they have been emptied.

14. Transport Information

Not a hazardous material for transportation.

**US DOT REGULATIONS:** 

NON-BULK Proper Shipping Name: Not regulated Proper Shipping Name: Not regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized safety officer. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

**CALIFORNIA PROPOSITION 65:** This product contains the following chemicals that are known to

the State of California to cause cancer, birth defects or other

reproductive harm.

Component CAS Number

None

Date Printed: 7/14/2015 Page 5 of 6

Product: U-835 Revised Date: 04/27/15 MSDS ID: R1102 Replaces Date: 12/16/13

TSCA INVENTORY STATUS: All components of this product are listed, or excluded from

listing, on the United States Environmental Protection Agency

Toxic Substances Control Act (TSCA) inventory.

SARA 313 TOXIC CHEMICALS: Component CAS Number Concentration

None

R Phrases: R 21/22 Harmful in contact w/ skin and if swallowed

R 36/37/38 Irritating to eyes, respiratory system and skin

S Phrases: S 26, 28 (soap and water), 36 wear suitable protective clothing

### 16. Other Information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgments of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. While that data contained herein is factual, it should not be taken as warranty or representation for which the company assumes legal responsibility. It is offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Date Printed: 7/14/2015 Page 6 of 6