Product: MM-204 Revised Date: 01/02/25 MSDS ID: R1173 Replaces Date: 04/24/23

1. General Information

Product Code: R1173 Trade Name(s): MM-204

Product Type: Acrylate Monomer Recommended Use: Reactive diluent None identified

Company: Designer Molecules, Inc.

10080 Willow Creek Rd. San Diego, CA 92131

Telephone: 858-348-1122

Emergency phone number (spill, leak, fire, exposure or accident):

US Domestic (800) 535-5053 (INFOTRAC) Includes Canada and Mexico

International +1 (352) 323-3500 China Specific (86) 400-120-0761 Germany Specific (49) 0800-181-2924 Australia Specific (61) 1-300-366-961

2. Hazards Identification

EMERGENCY OVERVIEW:

OSHA Hazards:

Respiratory sensitizer, Irritant

GHS Classification:

Respiratory sensitizer (Category 1)

Skin irritation (Category 2) Eye irritation (Category 2A) Skin sensitization (Category 1)

Specific target organ toxicity – single exposure (Category 3)

GHS Label Elements, including precautionary statements:





Signal Word: Danger

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

P280: Wear protective gloves.

P284: In case of inadequate ventilation wear respiratory protection.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P302 + P352 IF ON SKIN: Wash with soap and water.

Date Printed: 1/2/2025 Page 1 of 5

Product: MM-204 Revised Date: 01/02/25 MSDS ID: R1173 Replaces Date: 04/24/23

HMIS Classification:

Health Hazard: 2 Flammability: 1 Physical Hazards: 2

POTENTIAL HEALTH EFFECTS:

INHALATION: May be harmful if inhaled. Causes respiratory tract irritation and sensitization.

EYE CONTACT: Causes eye irritation

SKIN CONTACT: Harmful if absorbed through skin. Causes skin irritation.

SWALLOWING: Harmful if swallowed.

3. Composition Information

COMPONENT CAS# CONCENTRATION

Dicyclopentadiene Acrylate 33791-58-1 > 85%

Synonyms:

Acrylic acid, 3a,4,5,6,7,7a-hexahydro-4,7-methanoindenyl ester

2-Propenoic acid, 3a,4,5,6,7,7a-hexahydro-4,7-methano-1H-indenyl ester

4. First Aid Measures

SWALLOWING: Do not induce vomiting. Give person large amounts of water. Get immediate

medical attention.

SKIN CONTACT: Wash area with soap and water. Remove contaminated clothing and shoes. Wash

or clean before reuse.

INHALATION: Remove person to fresh air. If breathing has stopped, perform artificial respiration. If

breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: Flush with water for 15 minutes. Get immediate medical attention.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire and Explosion Hazard Data

FLASH POINT (method): 259°F / 126°C, (closed cup)

AUTOIGNITION: 824°F / 440°C

EXTINGUISHER METHOD: Water spray, CO₂, foam, dry chemical

SPECIAL FIRE-FIGHTING PROCEDURES:

Fire fighters should wear NIOSH/MSHA approved pressure demand self-contained breathing apparatus. Decontaminate or discard any clothing that may contain chemical residues.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Risk of violent self-polymerization if overheated in a container. Do not enter fire area without proper protection. See Section 10, Reactivity Data, for decomposition products possible. Fight fire from safe distance and protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Water may be ineffective in firefighting due to low solubility. Use water spray/fog for cooling. Pressure relief system may plug with solids, increasing risk of overpressure.

Date Printed: 1/2/2025 Page 2 of 5

Product: MM-204 Revised Date: 01/02/25 MSDS ID: R1173 Replaces Date: 04/24/23

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Promptly absorb spill. Remove sources of ignition. Cover drains to prevent entry into waterways. Wear personal protective equipment (clothing and gloves) when handling spilled materials.

PERSONAL PRECAUTIONS:

Wear suitable protective equipment.

ENVIRONMENTAL PRECAUTIONS:

This product is miscible in water. This material is resistant to rapid biodegradation. May be toxic to aquatic life. Avoid runoff to waterways and sewers.

7. Handling and Storage

HANDLING: Avoid contact with eyes.

Keep container closed.

Use with adequate ventilation. Wash thoroughly after handling.

VENTILATION: General (mechanical) room ventilation is expected to be satisfactory for use at room

temperature. Special, local ventilation is recommended at points where vapors generated

at high temperatures may be vented to the workplace air.

STORAGE: Store at 5°C away from incompatible materials identified in the Stability and Reactivity

Section.

8. Exposure Controls and Personal Protection Measures

EXPOSURE LIMITS:

None established by OSHA, ACGIH or UCC

PERSONAL PROTECTION:

Respiratory: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and

ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use. If a respirator is used, a NIOSH/MSHA approved respirator with organic vapor/dust-mist

fume filters represents the minimum level of respiratory protection.

Hands: Solvent impermeable gloves. Eyes: Chemical safety goggles. Skin: Chemical-resistant clothing.

OTHER PROTECTIVE EQUIPMENT:

Wear disposable protective clothing to facilitate recovery of any materials spilled.

ENGINEERING CONTROLS:

Ventilation:

Local Exhaust:

Fume hood at point of generation with sufficient exhaust to remove material from breathing zone.

Date Printed: 1/2/2025 Page 3 of 5

Product: MM-204 Revised Date: 01/02/25 MSDS ID: R1173 Replaces Date: 04/24/23

9. Physical / Chemical Characteristics

APPEARANCE:

Physical State: Liquid

Color: Colorless to yellow

Odor: Pungent

OTHER PROPERTIES:

Boiling Point: Approx 77°C Melting Point: Approx. -36°C

pH: Not currently available

Density (g/CC): 1.07

Vapor Pressure (mbar): 0.23 mbar @ 20°C Vapor Density (air=1): Not determined

Volatile Organic Compounds: ≈ 0%

Solubility in water: Not determined Evaporation rate: Not determined

Percent volatile (weight): $\approx 0\%$

Decomposition Temperature: Not determined

10. Reactivity Hazard Data

STABILITY: Stable with risk of self-polymerization if overheated.

CONDITIONS TO AVOID: Avoid heat. Avoid oxygen content above the products of less

than 5%. Do not blanket with nitrogen. Avoid UV light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged

storage.

INCOMPATIBLE MATERIALS: Radical formers, free radical initiators, peroxides, mercaptans,

nitro-compounds, perborates, azides, ether, ketones, amines, nitrates, oxidizing agents, reducing agents, strong bases, acid anhydrides, acid chlorides, concentrated mineral acids, metal

salts.

HAZARDOUS DECOMPOSITION PRODUCTS:

Acrid smoke-fumes/carbon monoxide/carbon dioxide and perhaps other toxic vapors may be released during a fire

involving this product.

HAZARDOUS POLYMERIZATION: Will occur.

11. Toxicological Information

ACUTE TOXICITY

Eye Contact: May cause eye irritation.

Skin Contact: May cause irritation. Prolonged and/or repeated contact may produce dermititis.

Skin PIS(Rbt) = 3. Derrmal LD50 (Rbt) > 5g/Kg

Inhalation: May cause irritation to the nose, throat and respiratory tract.

Ingestion: May cause irritation of the gastrointestinal tract. Oral LD50 (rat) = 10 g/Kg.

CHRONIC EFFECTS: Unknown

12. Ecological Information

POTENTIAL EFFECT ON ENVIRONMENT: Unknown MOBILITY: Miscible POTENTIAL TO BIOACCUMULATE: Unknown AQUATIC TOXICITY: Unknown

Date Printed: 1/2/2025 Page 4 of 5

Product: MM-204 Revised Date: 01/02/25 MSDS ID: R1173 Replaces Date: 04/24/23

13. Disposal Considerations

WASTE DISPOSAL METHOD: Disposal should be in accordance with local, state of

national legislation.

EMPTY CONTAINER WARNINGS: Empty containers may contain product residue, follow

MSDS and label warnings even after they have been

emptied.

14. Transport Information

Not a hazardous material for transportation.

US DOT REGULATIONS:

NON-BULK Proper Shipping Name: Not regulated Proper Shipping Name: Not regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized safety officer. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

CALIFORNIA PROPOSITION 65: This product contains the following chemicals that are known to

the State of California to cause cancer, birth defects or other

reproductive harm.

Component CAS Number

None

TSCA INVENTORY STATUS: Listed on the TSCA inventory.

SARA 313 TOXIC CHEMICALS: Component CAS Number

None

R Phrases: R 43 May cause sensitization by skin contact

R 36/37/38 Irritating to eyes, respiratory system and skin

S Phrases: S 26, 28 (soap and water), 36

16. Other Information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgments of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. While that data contained herein is factual, it should not be taken as warranty or representation for which the company assumes legal responsibility. It is offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Date Printed: 1/2/2025 Page 5 of 5