Product: EC-326 Revised Date: 09/01/22 MSDS ID: R1147 Replaces Date: 01/01/19

1. General Information

Product Code: R1147 Trade Name: EC-326

Product Type: Acetate/Proprionate Epoxy Curative

Recommended Use: Epoxy curative Restrictions: None identified

Company: Designer Molecules, Inc.

10080 Willow Creek Rd. San Diego, CA 92131

Telephone: 858-348-1122

Emergency phone number (spill, leak, fire, exposure or accident):

US Domestic 800-424-9300 (CHEMTREC)

International +1 703-527-3887

2. Hazards Identification

EMERGENCY OVERVIEW:

OSHA Hazards:

Harmful by ingestion, Irritant

GHS Classification:

Acute toxicity, Oral (Category 4) Skin Irritation (Category 2) Eye Irritation (Category 2A)

Specific target organ toxicity – single exposure (Category 3)

Acute aquatic toxicity (Category 1)
Chronic aquatic toxicity (Category 1)

GHS Label Elements, including precautionary statements:





Signal Word: Warning

H302: Harmful if swallowed. H315: Causes skin irritation.

H319: Causes serious eye irritation.H335: May cause respiratory irritation.

H410: Very toxic to aquatic life with long lasting effects.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P273: Avoid release to the environment.

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container to an approved waste disposal plant.

HMIS Classification:

Health Hazard: 2 Flammability: 0 Physical Hazards: 0

Date Printed: 8/31/2022 Page 1 of 5

 Product:
 EC-326
 Revised Date: 09/01/22

 MSDS ID:
 R1147
 Replaces Date: 01/01/19

NFPA Rating:

Health Hazard: 2 Fire: 0 Reactivity Hazard: 0

POTENTIAL HEALTH EFFECTS:

INHALATION: May be harmful if inhaled. Causes respiratory tract irritation.

EYE CONTACT: Causes eye irritation

SKIN CONTACT: Harmful if absorbed through skin. Causes skin irritation.

SWALLOWING: Harmful if swallowed.

3. Composition Information

Synonyms: Bisphenol A acetate propionate, R1147, EC-326

COMPONENT CAS# CONCENTRATION

Propanioc acid, mixed diesters with acetic acid and bisphenol A

936555-33-8 95%

4. First Aid Measures

SWALLOWING: Do not induce vomiting. Wash out mouth with water provided the person if fully

conscious. Get immediate medical attention.

SKIN CONTACT: Wash area with soap and water. Remove contaminated clothing and shoes. Wash

or clean before reuse.

INHALATION: Remove person to fresh air. If breathing has stopped, perform artificial respiration. If

breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: Flush with water for 15 minutes. Get immediate medical attention.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at

the control of symptoms and the clinical condition of the patient.

5. Fire and Explosion Hazard Data

FLASH POINT (method): >392°F / >200°C, (closed cup)

AUTOIGNITION: Not determined

EXTINGUISHER METHOD: Water spray, CO₂, foam, dry chemical

SPECIAL FIRE-FIGHTING PROCEDURES:

Fire fighters should wear NIOSH/MSHA approved pressure demand self-contained breathing apparatus. Decontaminate or discard any clothing that may contain chemical

residues.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None.

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Promptly absorb spill. Remove sources of ignition. Cover drains to prevent entry into waterways. Wear personal protective equipment (clothing and gloves) when handling spilled materials.

PERSONAL PRECAUTIONS:

Wear suitable NIOSH-approved protective equipment.

Date Printed: 8/31/2022 Page 2 of 5

Product: EC-326 Revised Date: 09/01/22 MSDS ID: R1147 Replaces Date: 01/01/19

ENVIRONMENTAL PRECAUTIONS:

May be toxic to aquatic life. Avoid runoff to waterways and sewers.

7. Handling and Storage

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

For small amounts, wipe off with damp sponge. For large amounts, absorb on sand or vermiculite. Wipe off and dispose of into proper waste disposal containers.

WASTE DISPOSAL METHODS:

Dissolve or mix material with proper solvent and incinerate.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Material is generally stable. Keep away from open flames. Store at room temperature in a cool dry place

OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS:

None.

8. Exposure Controls and Personal Protection Measures

PERSONAL PROTECTION:

Respiratory: Use respirators and components tested and approved under appropriate

government standards such as NIOSH (US) or CEN (EU).

Hands: Protective gloves are recommended (4H, butyl, neoprene, nitrile, or PVC-

coated).

Eyes: Safety glasses, goggles, or face shields are required.

Skin: Chemical-resistant clothing.

OTHER PROTECTIVE EQUIPMENT:

Eye bath. Safety shower.

ENGINEERING CONTROLS:

Ventilation: This product should be stored in a closed environment to prevent any

vapors from escaping storage containers, and to prevent moisture contamination. General mechanical room ventilation is satisfactory. Local ventilation is required at points where vapors are likely to be released into

workplace air.

EXPOSURE LIMITS:

<u>Component</u> <u>Type</u> <u>Value</u> <u>Remarks</u>

Modified Bis A TWA (skin) OSHA - ppm None established STEL (skin) ACGIH - ppm None established

TWA (skin) ACGIH - ppm None established

9. Physical / Chemical Characteristics

APPEARANCE:

Physical State: Solid

Color: White to light yellow Odor: Mild vinegar odor

OTHER PROPERTIES:

Boiling Point: Not determined

Date Printed: 8/31/2022 Page 3 of 5

Product: EC-326 Revised Date: 09/01/22 MSDS ID: R1147 Replaces Date: 01/01/19

Melting Point: Not applicable (m.p. = 41°C if material has been allowed to

freeze)

pH: Not applicable

Specific Gravity (H₂O=1): 1.12

Vapor Pressure:

Vapor Density (Air-1):

Solubility in water:

Not determined

Heavier than air.

Not determined

Evaporation rate (BuAc=1): <1

Avg. Molecular Weight:

Percent volatile (weight):

Percent volatile (volume):

Volatile organic content:

Not established

Not determined

Not determined

10. Reactivity Hazard Data

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, high temperatures

INCOMPATIBLE MATERIALS: Strong acids or bases; strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon dioxide (CO2), carbon monoxide (CO)

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Open flames; strong oxidizing agents

11. Toxicological Information

ROUTE OF EXPOSURE:

Inhalation: Material is irritating to mucous membranes and upper respiratory tract.

Multiple Routes: Causes eye and skin irritation. May be harmful by inhalation, ingestion, or skin absorption.

SIGNS AND SYMPTOMS OF EXPOSURE:

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. Ecological Information

ELIMINATION (persistance and degradability):

Biodegradability: Not determined

AQUATIC TOXICITY:

Acute toxicity to fish: Not determined

Acute toxicity to

plants: Not determined Microorganisms: Not determined.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Disposal should be in accordance with local, state of

national legislation.

EMPTY CONTAINER WARNINGS: Empty containers may contain product residue, follow

MSDS and label warnings even after they have been emptied.

Date Printed: 8/31/2022 Page 4 of 5

Product: EC-326 Revised Date: 09/01/22 MSDS ID: R1147 Replaces Date: 01/01/19

14. Transport Information

Not a hazardous material for transportation.

US DOT REGULATIONS:

NON-BULK Proper Shipping Name: Not regulated Proper Shipping Name: Not regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized safety officer. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

CA PROPOSITION 65: This material does not contain any chemicals known to the State of

California to cause cancer or reproductive defects.

TSCA INVENTORY STATUS: Material is manufactured under a Low Volume Exemption (LVE)

in compliance with Section 5 (h)(4) of the Toxic Substances

Control Act, 15 U.S.C.

TSCA 12(b) EXPORT NOTIFICATION: This material does not contain 12(b) regulated chemicals.

SARA 311/312 HAZARD CLASS: There are no known hazards associated with this material.

EINECS IDENTIFICATION: This material is not listed on EINECS.

16. Other Information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgments of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. While that data contained herein is factual, it should not be taken as warranty or representation for which the company assumes legal responsibility. It is offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Date Printed: 8/31/2022 Page 5 of 5