Product: EC-861 Revised Date: 03/07/19 MSDS ID: R1165 Replaces Date: 09/18/12

1. Product and Company Identification

Product Code: R1165 Trade Name(s): EC-861 Product Type: Ester

Recommended Use:

Restrictions: None identified

Company: Designer Molecules, Inc.

10080 Willow Creek Rd. San Diego, CA 92131

Telephone: 858-348-1122

Emergency phone number (spill, leak, fire, exposure or accident):

US Domestic (800) 535-5053 (INFOTRAC) Includes Canada and Mexico

International +1 (352) 323-3500 China Specific (86) 400-120-0761 Germany Specific (49) 0800-181-2924 Australia Specific (61) 1-300-366-961

2. Hazards Identification

EMERGENCY OVERVIEW: WARNING

EYE IRRITANT HARMFUL IF SWALLOWED SKIN SENSITIZER

Yellow liquid, faint musty odor

POTENTIAL HEALTH EFFECTS:

EFFECTS OF SINGLE ACUTE OVEREXPOSURE:

HMIS ratings (scale 0-4)

Hazardous Materials Identification System

Health (acute effects) = * 2
Flammability = 1
Physical = 1
Personal Protection = B

INHALATION: Short-term harmful health effects are not expected from vapor generated at ambient

temperature. Vapors and/or aerosols that may be formed at elevated temperatures may be irritating to eyes and respiratory tract. Avoid breathing vapors or mists.

EYE CONTACT: May cause eye irritation. Contact with eyes causes redness and discomfort that is

transient.

SKIN CONTACT: Brief contact may cause slight irritation with itching and local redness. Repeated

and/or prolonged contact may cause skin sensitization.

SKIN ABSORPTION: No evidence of harmful effects from available information.

SWALLOWING: Ingestion may cause abdominal discomfort, nausea, vomiting, and diarrhea.

3. Composition Information

COMPONENT	CAS#	CONCENTRATION
Proprietary Ester Toluene	1071523-12-0 108-88-2	> 90% < 0.5%

Date Printed: 1/29/2021 Page 1 of 6

Product: EC-861 Revised Date: 03/07/19 MSDS ID: R1165 Replaces Date: 09/18/12

4. First Aid Measures

SWALLOWING: Do not induce vomiting. Give person large amounts of water. Get immediate

medical attention.

SKIN CONTACT: Wash area with soap and water. Remove contaminated clothing and shoes. Wash

or clean before reuse.

INHALATION: Remove person to fresh air. If breathing has stopped, perform artificial respiration. If

breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: Flush with water for 15 minutes. Get immediate medical attention.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire and Explosion Hazard Data

FLASH POINT (method): > 201°C (394°F) (closed cup) **EXTINGUISHER METHOD:** Water, CO₂, foam, dry chemical

FLAMMABLE LIMITS %:

Lower: Not determined Upper: Not determined

SPECIAL FIRE-FIGHTING PROCEDURES:

Fire fighters should wear NIOSH/MSHA approved pressure demand self-contained breathing apparatus. Decontaminate or discard any clothing that may contain chemical residues.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Do not enter fire area without proper protection. See Section 10, Reactivity Data, for decomposition products possible. Fight fire from safe distance and protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Water may be ineffective in firefighting due to low solubility. Use water spray/fog for cooling. Pressure relief system may plug with solids, increasing risk of overpressure.

6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Promptly absorb spill. Remove sources of ignition. Cover drains to prevent entry into waterways. Wear personal protective equipment (clothing and gloves) when handling spilled materials.

PERSONAL PRECAUTIONS:

Wear suitable protective equipment.

ENVIRONMENTAL PRECAUTIONS:

This product is essentially insoluble in water. This material is resistant to rapid biodegradation. May be toxic to aquatic life. Avoid runoff to waterways and sewers.

Date Printed: 1/29/2021 Page 2 of 6

Product: EC-861 Revised Date: 03/07/19 MSDS ID: R1165 Replaces Date: 09/18/12

7. Handling and Storage

HANDLING: Avoid contact with eyes.

Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

VENTILATION: General (mechanical) room ventilation is expected to be satisfactory for use at room

temperature. Special, local ventilation is recommended at points where vapors generated

at high temperatures may be vented to the workplace air.

STORAGE: Store in a sealed container out of direct sunlight at room temperature and away from

incompatible materials identified in the Stability and Reactivity Section.

8. Exposure Controls and Personal Protection Measures

COMPONENT EXPOSURE LIMITS

ACGIH OSHA MFG Working

Standard

Toluene 20 ppm TWA 300 ppm Ceiling

200 ppm TWA

PERSONAL PROTECTION:

Respiratory: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and

ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use. If a respirator is used, a NIOSH/MSHA approved respirator with organic vapor/dust-mist

fume filters represents the minimum level of respiratory protection.

Hands: Solvent impermeable gloves. Eyes: Chemical safety goggles. Skin: Chemical-resistant clothing.

OTHER PROTECTIVE EQUIPMENT:

Wear disposable protective clothing to facilitate recovery of any materials spilled.

ENGINEERING CONTROLS:

Ventilation: Local Exhaust:

Fume hood at point of generation with sufficient exhaust to remove material

from breathing zone.

EXPOSURE LIMITS:

None established by OSHA, ACGIH or UCC

9. Physical / Chemical Characteristics

APPEARANCE:

Physical State: Liquid Color: Yellow

Odor: Faint musty odor

OTHER PROPERTIES:

Boiling Point:

Melting Point:

Not determined.

Not determined.

Not currently available

Density (g/CC): 0.996

Vapor Pressure (mmHg): Not determined Vapor Density (air=1): Not determined

Volatile Organic Compounds: < 1%

Date Printed: 1/29/2021 Page 3 of 6

Product: EC-861 Revised Date: 03/07/19 MSDS ID: R1165 Replaces Date: 09/18/12

Solubility in water: Not determined Evaporation rate: Not determined

Percent volatile (weight): < 1%%

Decomposition Temperature: Not determined

10. Reactivity Hazard Data

STABILITY: Stable

CONDITIONS TO AVOID: Elevated temperatures

INCOMPATIBLE MATERIALS: Incompatible with strong oxidizing, strong reducers

HAZARDOUS DECOMPOSITION PRODUCTS:

Acrid smoke-fumes/carbon monoxide/carbon dioxide and perhaps other toxic vapors may be released during a fire

involving this product.

HAZARDOUS POLYMERIZATION: Will not occur during normal storage and handling.

11. Toxicological Information

ROUTE OF ENTRY: Inhalation; Ingestion; Eye Contact; Skin Contact

CARCINOGEN: There is no evidence that this product poses a carcinogenic risk under

normal conditions of handling and use.

PRODUCT TOXICOLOGY

PRODUCT INFORMATION: Low acute toxicity under normal handling and use.

ACUTE EFFECTS OF EXPOSURE: May cause irritation to eyes and respiratory system. High exposure may cause anesthesia and irregular heartbeat due to the heart's increased sensitivity to

adrenaline

CHRONIC EFFECTS OF EXPOSURE: The toxicological properties of this product have not bee fully evaluated. Use of good industrial hygiene practices is required. Avoid direct contact with skin or eyes. Do not ingest or inhale.

TARGET ORGANS: Eyes, skin POSSIBLE BIRTH DEFECT HAZARD: Yes

COMPONENT ORAL TOXICITY NOTES ON ORAL TOXICITY

Toluene Oral LD50: Rat 636 mg/kg Ingestion may cause irritation of the gastrointestinal tract. Aspiration of the product into the lungs following ingestion may cause pulmonary injury leading to pneumonitis. May cause nausea, vomiting and diarrhea.

COMPONENT DERMAL TOXICITY NOTES ON DERMAL TOXICITY

Toluene Dermal LD50: Rabbit 12124 mg/kg Mild irritant to skin. May be absorbed through skin. Repeated or prolonged contact may cause defatting of the skin resulting in dryness, cracking and dermatitus.

COMPONENT INHALATION TOXICITY NOTES ON INHALATION TOXICITY

Toluene Inhalation LC50 (4hr.)

Rat 49 g/m³, Mouse 400 ppm May cause irregular heartbeat. The vapor has anesthetic properties when inhaled at concentrations above the occupational exposure limit, it may cause respiratory irritation, headache, fatigue, dizziness and incoordination. Avoid breathing vapor or mists.

Date Printed: 1/29/2021 Page 4 of 6

Product: EC-861 Revised Date: 03/07/19 MSDS ID: R1165 Replaces Date: 09/18/12

12. Ecological Information

POTENTIAL EFFECT ON ENVIRONMENT: Do not allow to enter drains, sewers or watercourses.

MOBILITY: Insoluble POTENTIAL TO BIOACCUMULATE: Unknown

AQUATIC TOXICITY: None established

13. Disposal Considerations

WASTE DISPOSAL METHOD: Disposal should be in accordance with local, state of

national legislation.

EMPTY CONTAINER WARNINGS: Empty containers may contain product residue, follow

MSDS and label warnings even after they have been emptied.

14. Transport Information

Not a hazardous material for transportation.

US DOT REGULATIONS:

NON-BULK Proper Shipping Name: Not regulated Proper Shipping Name: Not regulated

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized safety officer. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

CALIFORNIA PROPOSITION 65: This product contains the following chemicals that are known to

the State of California to cause cancer, birth defects or other

reproductive harm.

Component CAS Number Toluene 108-88-3

TSCA INVENTORY STATUS: All components of this product are listed, or excluded from

listing, on the United States Environmental Protection Agency

Toxic Substances Control Act (TSCA) inventory.

SARA 313 TOXIC CHEMICALS: Component CAS Number

Toluene 108-88-3

R Phrases: R 36, 38, 43

R 36/37/38 Irritating to eyes, respiratory system and skin

S Phrases: S 26, 28 (soap and water), 36

Date Printed: 1/29/2021 Page 5 of 6

Product: EC-861 Revised Date: 03/07/19
MSDS ID: R1165 Replaces Date: 09/18/12

16. Other Information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgments of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. While that data contained herein is factual, it should not be taken as warranty or representation for which the company assumes legal responsibility. It is offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Date Printed: 1/29/2021 Page 6 of 6