

## DESCRIPTION

A-1100 is a proprietary non-halogenated additive designed to reduce resin bleed out on a variety of surfaces with minimal or no affect on the adhesion properties of the formulation. It shows excellent results when used in non-metal filled systems after reducing bleed. It is co-curable in free-radical polymerization. It also can enhance the rheological properties of various filled adhesives.

## HIGHLIGHTS

• Excellent bleed control	• Minimal adhesion degradation
• Co-curable in free-radical polymerization	• Non-halogenated

## TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	METHOD	RESULT
Appearance at Room Temperature	Visual	Yellow Liquid
Viscosity @ 25°C (typical)	Haake Rheometer	475 cP
Density		1.01 g/cc
Flash Point	Closed Cup	> 146°C
Recommended Storage Temp		10°C or below

*Data is for reference only and may vary depending on testing method used.*

## RECOMMENDED FORMULATION USE:

The A-1100 is recommended for use as an additive to reduce resin bleed out specifically on metal surfaces. The recommended addition of the A-1100 to a formulation is between 0.5% - 1% weight percent of resin. It shows superior bleed control in formulations that contain non-metal fillers such as silica.

## CONTACT:

### REQUEST A SAMPLE OR PLACE AN ORDER

Customer Support

☎ 858-348-1122

✉ [support@designermoleculesinc.com](mailto:support@designermoleculesinc.com)

REF: DMI Part Number: A6265